

Auto C-Pap System

ResPlus C-Pap



Technical Specifications

Mode	CPAP
Pressure Range	4 to 20 cmH ₂ O (hPa)
Pressure Accuracy	0 to 60 Min (5-min increments)
Ramp Time	4 cmH ₂ O to CPAP Pressure (CPAP)
Starting Ramp Pressure	0 to 3
Expiratory Pressure Relief	Automatic
Leak Compensation	Automatic
Altitude Compensation	0 to 5
Humidification	SD card & on Board : > 1 Year
Data Storage Capacity	14x15.6x9.4cm (w/o humidifier)
Dimensions	26.2x15.6x9.4cm (w/ humidifier)
Weight	950g (w/o humidifier)
	1500g (w/ humidifier)
	100-240 VAC, 50/60Hz, 2.0-1.0A
Electrical Requirements	<30dB @ 10 cmH ₂ O
Noise Level	PC Based
Data Analysis Software	Reusable Pollen
Filter	20mm, 6ft. (1.8m)
Tubing	Control Dial/Push Button
Device Controls	Chinese/English/Spanish
Language	5° to 35°C (41° to 95° F)
Operating Temperature	-20° to 60° C (-4° to 140° F)
Relative Humidity (Operating & Storage)	10 to 93% (Non-Condensing)
Atmospheric Pressure	101 to 77 kPa (0-2286 m/0-7500 ft)
Risk Classification	Class IIa, Type BF, IP22